

产品规格

产品名	T335/B335	T340	T365/B365	T390	T425/B425
分辨率	320 x 240	320 x 240	320 x 240	320 x 240	320 x 240
温度分辨率(30°C)	0.05°C	0.08°C	0.05°C	0.08°C	0.05°C
温度范围	-20°C~650°C	-20°C~350°C	-20°C~650°C	-20°C~1200°C	-20°C~1200°C
高温选择	~1200°C	~1200°C	~1200°C	-	-
Spot Meter	5	5	5	5	5
区域	5	5	5	5	5
变焦	2	4	4	8	8
融合	-	●(区间)	●(区间)	●(区间/以上/以下)	●(区间/以上/以下)
画中画	●	●(可移动)	●(可移动)	●(可移动)	●(可移动)
文本(从文件选择)	●	●	●	●	●
文本(触摸屏)	●	●	●	●	●
音声批注	●	●	●	●(Bluetooth)	●(Bluetooth)
图像标记	●	●	●	●	●
略图批注	-	●	●	●	●
区间功能	-	-	-	●	●
帧时	30Hz	60Hz	30Hz	60Hz	30Hz
筛选功能	-	●	●	●	●
即时报告创建(机内)	-	-	●	●	●
FLIR QuickReport	●	●	●	●	●